

(I) **ATTENZIONE!**

**Togliere la corrente prima di eseguire qualsiasi collegamento elettrico o sostituire le lampadine.**

- 1) **Fig.1** - Infilare i vetri **1** e **2**, ed avvitare la rondella **A** e il gancio **B** fissandolo in testa alla tige **C** mediante l'apposita vite.
- 2) **Fig.2** - Agganciare la catena a soffitto con il rosone **3** abbassato e poi il gancio **B** con il moschettone **D**.
- 3) Far passare il cavo elettrico tra gli anelli della catena e il tubetto **E**.
- 4) **Fig.3** - Eseguire il collegamento elettrico alla linea di alimentazione con gli appositi morsetti ed alzare il rosone **3** a soffitto fissandolo con il fondello **F**.
- 5) Infilare il vetro **4** sostenendolo con la rondella **G** ed avvitare la borchia **H**.

**1**

(GB) **WARNING!**

**Switch off the current before connecting or relamping**

- 1) **Fig.1** - Insert glasses **1** and **2**, then screw washer **A** and fasten closed ring **B** on the top of stem **C**.
- 2) **Fig.2** - Hook the chain to ceiling by dropping glass canopy **3** then hook **B** to spring ring **D**.
- 3) Pass the golden cable through the rings of chain and inside tube **E**.
- 4) **Fig.3** - Connect the fixture wires to supply wires with proper terminals and push up canopy **3** to ceiling then fix canopy to tube **E** with screw **F**.
- 5) Mount glass **4** by holding it with washer **G** and screwing stud **H**.

**1**

(USA) **WARNING!**

**Switch off the current before connecting or relamping**

**RISK OF FIRE AND ELECTRIC SHOCK. THIS PRODUCT IS TO BE INSTALLED BY A QUALIFIED ELECTRICIAN ONLY.**

- 1) **Fig.1** - Insert glasses **1** and **2**, then screw washer **A** and fasten closed ring **B** on the top of stem **C**.
- 2) **Fig.2** - Mount the support **E** with the crossbar to outlet box to the ceiling by dropping glass canopy **4** then hook **B** to spring ring **D**.
- 3) Pass the golden cable through the rings of chain and inside tube **E**.
- 4) **Fig.3** - Connect ground supply wire to ground (yellow/green) fixture wire then black to line (black) and white to white with wirenuts (see circuit diagram) and push up canopy **3** to ceiling then fix canopy to tube **E** with screw **F**.
- 5) Mount glass **4** by holding it with washer **G** and screwing stud **H**.




Fig.1




Fig.2




Fig.3

**r** 4430/DO FANALE VENEZIANO  
**r** 4430/OO  
**r** 4430/VO

**h.** - height cm 53 - 20 3/4"  
**Æ**- width cm 25 - 9 3/4"  
**Kg.** - pounds 6 - 13.2  
**r** 100 - 120V **r** 220 - 240V  
50Hz ~ 60Hz

**1 x max 100W**

E27 **r** E26 **r** (medium base)

**Cl. I**

lampadina chiara/clear bulb: DO, OO.

lampadina opale/white bulb: OB, RO, PO.



Agg: 27/06/2005