

(I) **ATTENZIONE!**

Togliere la corrente prima di eseguire qualsiasi collegamento elettrico o sostituire le lampadine.

- 1) **Fig.1** - Infilare i vetri **1** e **2**, ed avvitare la rondella **A** e il gancio **B** fissandolo in testa alla tige **C** mediante l'apposita vite.
- 2) **Fig.2** - Agganciare la catena a soffitto con il rosone **3** abbassato e poi il gancio **B** con il moschettone **D**.
- 3) Far passare il cavo elettrico tra gli anelli della catena e il tubetto **E**.
- 4) **Fig.3** - Eseguire il collegamento elettrico alla linea di alimentazione con gli appositi morsetti ed alzare il rosone **3** a soffitto fissandolo con il fondello **F**.
- 5) Infilare il vetro **4** sostenendolo con la rondella **G**, poi il vetro **5** ed avvitare la borchia **H**.

1

(GB) **WARNING!**

**Switch off the current before connecting or relamping**

- 1) **Fig.1** - Insert glasses **1** and **2**, then screw washer **A** and fasten closed ring **B** on the top of stem **C**.
- 2) **Fig.2** - Hook the chain to ceiling by dropping glass canopy **3** then hook **B** to spring ring **D**.
- 3) Pass the golden cable through the rings of chain and inside tube **E**.
- 4) **Fig.3** - Connect the fixture wires to supply wires with proper terminals and push up canopy **3** to ceiling then fix canopy to tube **E** with screw **F**.
- 5) Mount glass **4** by holding it with washer **G** then glass **5** and screwing stud **H**.

1

(USA) **WARNING!**

**Switch off the current before connecting or relamping**

- 1) **Fig.1** - Insert glasses **1**, **2** and **3**, then screw washer **A** and fasten closed ring **B** on the top of stem **C**.
- 2) **Fig.2** - Mount the support **E** with the crossbar to outlet box to the ceiling by dropping glass canopy **4** then hook **B** to spring ring **D**.
- 3) Pass the golden cable through the rings of chain and inside tube **E**.
- 4) **Fig.3** - Connect ground supply wire to ground (yellow/green) fixture wire then black to line (black) and white to white with wire nuts (see circuit diagram) and push up canopy **4** to ceiling then fix canopy to tube **E** with screw **F**.
- 5) Mount glass **5** by holding it with washer **G** then the glass finial and fix it by screwing stud **H**.





Fig.1

Fig.2

Fig.3

Sospensioni e Fanali

**FANALE**

**VENEZIANO**

r 5383/DO

r 5383/OB

r 5383/OO

r 5383/VO

h. cm 53 - 20 7/8"

Ø. cm 40 - 15 3/4"

Kg. ~ 7 - 15,4 pound

100 - 120V r 220 - 240V r

50Hz~60Hz

1 x max100W

E27 r E26 r (medium base)

Cl. I

lampadina chiara/clear bulb



Agg: 29/01/2002